



R3250

RIGID COUPLINGS

Material

Stainless steel (A2, AISI 303) or anodised aluminium (DIN 3,1355).

Technical Notes

Some sizes may be full, semi-counter-bored, or step cut.

Order No.	Material	d_1 +0.025 -0.0	d_2	r_1	w_1	For shaft
R3250.031-AL	Aluminium	4.6	14.0	8.5	4.0	3
R3250.032-AL	Aluminium	4.6	16.0	8.5	4.0	3
R3250.033-AL	Aluminium	4.6	16.0	8.5	5.0	3
R3250.034-AL	Aluminium	4.6	16.0	10.0	6.5	3
R3250.051-AL	Aluminium	6.6	16.0	8.5	4.0	5
R3250.052-AL	Aluminium	6.6	16.0	8.5	5.0	5
R3250.053-AL	Aluminium	6.6	22.0	12.5	5.0	5
R3250.054-AL	Aluminium	6.6	22.0	13.0	6.0	5
R3250.072-AL	Aluminium	8.6	22.0	13.0	6.0	7
R3250.081-AL	Aluminium	9.6	28.5	16.0	6.5	8
R3250.082-AL	Aluminium	9.6	28.5	16.0	8.0	8
R3250.101-AL	Aluminium	11.6	28.5	16.0	6.5	10
R3250.102-AL	Aluminium	11.6	32.0	16.0	8.0	10
R3250.121-AL	Aluminium	13.6	32.0	16.0	8.0	12
R3250.031-A2	Stainless	4.6	14.0	8.5	4.0	3
R3250.032-A2	Stainless	4.6	16.0	8.5	4.0	3
R3250.033-A2	Stainless	4.6	16.0	8.5	5.0	3
R3250.034-A2	Stainless	4.6	16.0	10.0	6.5	3
R3250.041-A2	Stainless	5.6	16.0	8.5	4.0	4
R3250.051-A2	Stainless	6.6	16.0	8.5	4.0	5
R3250.052-A2	Stainless	6.6	16.0	8.5	5.0	5
R3250.053-A2	Stainless	6.6	22.0	12.5	5.0	5
R3250.054-A2	Stainless	6.6	22.0	12.5	6.0	5
R3250.061-A2	Stainless	7.6	22.0	12.5	5.0	6
R3250.071-A2	Stainless	8.6	22.0	12.5	5.0	7
R3250.072-A2	Stainless	8.6	22.0	13.0	6.0	7
R3250.081-A2	Stainless	9.6	28.5	16.0	6.5	8
R3250.082-A2	Stainless	9.6	28.5	16.0	8.0	8
R3250.101-A2	Stainless	11.6	28.5	16.0	6.5	10
R3250.102-A2	Stainless	11.6	32.0	16.0	8.0	10
R3250.121-A2	Stainless	13.6	32.0	16.0	8.0	12