



## R3252

RIGID COUPLINGS

### Material

Stainless steel (AISI 303 or AISI 416) or mild steel.

Order No.	Material	$l_1$	$d_1$	$h_1$	$r_1$	$w_1$ $\pm 0.13$	Finish	For shaft
R3252.031	416 s/s	7.9	4.6	17.5	11.1	6.35	Black Pass.	3.0
R3252.032	303 s/s	7.9	4.6	17.5	11.1	6.35	Clear Pass.	3.0
R3252.033	Steel	7.9	4.6	17.5	11.1	3.56	Cad. Plate	3.0
R3252.051	416 s/s	9.6	6.6	20.6	13.1	6.35	Black Pass.	5.0
R3252.052	303 s/s	9.6	6.6	20.6	13.1	6.35	Clear Pass.	5.0
R3252.053	Steel	9.6	6.6	20.6	13.1	3.56	Cad. Plate	5.0
R3252.071	416 s/s	11.1	8.6	20.6	14.3	6.35	Black Pass.	7.0
R3252.072	303 s/s	11.1	8.6	20.6	14.3	6.35	Clear Pass.	7.0
R3252.073	Steel	11.1	8.6	20.6	14.3	3.56	Cad. Plate	7.0
R3252.101	416 s/s	15.9	11.6	26.2	17.1	6.35	Clear Pass.	10.0
R3252.102	Steel	15.9	11.6	26.2	17.1	6.35	Cad. Plate	10.0
R3252.103	Steel	15.9	11.6	26.2	17.1	3.56	Cad. Plate	10.0
R3252.121	416 s/s	15.9	13.6	26.2	17.1	6.35	Clear Pass.	12.0
R3252.122	Steel	15.9	13.6	26.2	17.1	6.35	Cad. Plate	12.0
R3252.123	Steel	15.9	13.6	26.2	17.1	3.56	Cad. Plate	12.0